

ITS120DIN

DESCRIPTION

The ITS120DIN is your best option for a compact, Din Rail mounted surge protection device. The unit offers L-N, L-G, and N-G protection.

The unit includes remote contacts to monitor the status of the ITS120DIN. This product also incorporates a modular design. The protective module is easily replaced if the green operating lamp is extinguished.

SPECIFICATIONS

Operating Voltage.....	120 VAC
Maximum Continuous Operating Voltage.....	150 VAC
Voltage Protection Level.....L-N	>1100V
.....L-G / N-G.....	>1200V
Maximum Discharge Current (per mode).....	10kA
Response Time.....	<25ns
Temperature Range.....	-40°C to +85°C
Mounting.....	Snaps to 35mm Rail
Weight.....Total.....	0.20 lbs
.....Replacement Module.....	0.07 lbs
Limited Warranty.....	5 Year




FEATURES


- Modular Design
- 35 mm Din Rail Mount
- High Energy MOV and GDT Design
- Thermally Protected MOVs
- Operating Status Indication
- Immediately Self-Restores After Each Surge

DIMENSIONS (mm)

ITS120DIN



ITS120DIN-P Replacement Module



HESCO/RLS

220 Springview Commerce Drive
Unit 190
DeBary, FL 32713

For more information and product support call us at...

1-800-547-4868