

## ITS24DIN

### DESCRIPTION

The ITS24DIN is your best option for a compact, Din Rail mounted surge protection device. The unit offers L-N, L-G, and N-G protection.

The unit includes remote contacts to monitor the status of the ITS24DIN. This product also incorporates a modular design. The protective module is easily replaced if the green operating lamp is extinguished.

### SPECIFICATIONS

Operating Voltage.....	24 VAC
Maximum Continuous Operating Voltage.....	34 VAC
Voltage Protection Level.....L-N .....	>250V
.....L-G / N-G.....	>700V
Maximum Discharge Current (per mode).....	2kA
Response Time.....	<25ns
Nominal Frequency.....	50 - 60 Hz
Temperature Range.....	-40°C to +85°C
Mounting.....	Snaps to 35mm Rail
Weight.....Total.....	0.20 lbs
.....Replacement Module.....	0.07 lbs
Limited Warranty.....	5 Year

**HESCO/RLS**  
 220 Springview Commerce Drive  
 Unit 190  
 DeBary, FL 32713

**For more information and product support call us at...**

**1-800-547-4868**




### FEATURES

- Modular Design
- 35 mm Din Rail Mount
- High Energy MOV and GDT Design
- Thermally Protected MOVs
- Operating Status Indication
- Immediately Self-Restores After Each Surge

### DIMENSIONS (mm)

ITS24DIN



ITS24DIN-P Replacement Module

